



Vicinity™ Workstation Screens are manufactured by Autex Industries Ltd and Autex Australia Pty Ltd under an ISO 9001 certified Quality Management System and an ISO 14001 Environmental Management System. The product is guaranteed to be free from manufacturing defects and carries a Manufacturer's Guarantee for a period of no less than ten years to meet all of the performance properties stated within this guarantee.

Specification

Product name Vicinity™ Workstation Screens
Description 100% polyester lightweight semi-rigid panel,
100% recycled polyester Workstation Clamp

	Metric	
Dimensions	Please refer to product data sheet for individual style dimensions	
Thickness	12 mm	24 mm
Tolerance	(+/- 6%)	(+/- 6%)

Physical description / properties

Boiling point:	N/A
Melting point:	250°C
Vapour pressure:	N/A
Specific gravity:	Polyester 1.38
Flash point:	N/A
Explosive limits:	N/A
Solubility in water:	Not soluble
Alkalinity:	pH 7.8
Relative vapour density:	N/A

Acoustic performance

Vicinity Workstation Screens are specifically designed to help improve acoustic privacy reduce and reduce noise levels.

Acoustic performance is estimated from the results of a suspended full panel tested according to ISO 354 in a reverberation room. Results have been calculated at one-third octave bands centred on 250 Hz, 500 Hz, 1000 Hz and 2000 Hz. and rounded to the nearest 0.05. All results are reported in metric sabin - per unit.

Frequency (Hz)	125	250	500	1000	2000	4000	Metric sabin per unit
● Haven (1600 mm/1800 mm)	0.50	1.00	1.40	1.65	2.10	2.35	1.55
● Hedge (600 mm)	0.30	0.65	0.90	1.10	1.35	1.50	1.00
● Hedge (1800 mm)	0.35	0.75	1.00	1.20	1.55	1.75	1.10
● Modesty (600 mm/1800 mm)	0.30	0.80	1.00	1.20	1.50	1.70	1.10
● Nook (1600 mm/1800 mm)	0.50	1.00	1.40	1.65	2.10	2.35	1.55
● Sol (600 mm)	0.10	0.20	0.25	0.35	0.40	0.45	0.30



Product specifications

Composition

100% polyester fibre from polyethylene terephthalate (PET). Vicinity Workstation Screens contain a minimum of 79% previously recycled polyester fibre.

Suitable applications

Suitable for most desks in a variety of workspaces, including: commercial and home offices, classrooms, and libraries.

Fire ratings

Vicinity Workstation Screens are a product made from Cube™ as the base material. Cube has been evaluated using the following test methods:

ISO 9705: 1993

Classification: Group 1-S
Smoke Production Rate:
<5.0m²/s

As required by NZBC C/VM2

AS ISO 9705 - 2003

Classification: Group 1
(SMOGR_{arc}): <100m²/s²
Assessed using methodology AS ISO 9705 - 2003 in accordance with AS 5637:2015, as required by NCC Specification 7: Fire Hazard properties: S7C4 FI 4974
FAR 4055

BS EN 13501-1:2018

Wall applications
Classification: B-s2,d0
(Cube 12 mm)

Tested using BS EN ISO 11925-2:2020 and BS EN 13823:2020 and classified in accordance with BS EN 13501-1:2018, as required by BS EN 15102:2007 + A1:2011. EUI-20-000268-A

BS EN 1021-1

Result: Pass (Cigarette)
1362214.7

ASTM E-84-15a

Class A, FS:0 - SD:45
(Cube 1/2")
RJ4479-2

VOC emissions

Autex polyester has been tested for chemical emissions in accordance with ASTM D5116 and is considered a low VOC product.
VOC concentration:
0.009 mg/m³ (7 days)

Water vapour sorption

ASTM C1104 / C1104M-13a
Test conditions: 49°C, 95%RH
Water vapour absorbed and adsorped after 4 days:
0.4% by weight

Microbial resistance

ASTM G21-15
Growth Rating: 0 (No growth)
Vicinity Workstation Screens do not promote the growth of moulds and mildew.

Colour fastness to light

Vicinity Workstation Screens are suitable for indoor use only. Light fastness is dependent on use and exposure. Vicinity has been evaluated to the following standard:
ISO 105-B02:2014
Rating: 6 (Highest = 7)

Colour fastness to rubbing

SO 105-X12:2016
Dry Rating: 4-5 (Highest = 5)
Wet Rating: 4-5 (Highest = 5)

Fabric care

Blot spills from fabric quickly. Wipe with a damp cloth. Avoid rubbing and using excessive amounts of water as this will affect the finish.

Use carpet or upholstery shampoo as directed. Blot with a clean, dry cloth after each application of the solution. Custom printed Vicinity requires the services of a specialist cleaning company. Refer to the Autex Acoustics® Care and Maintenance Guide for more information.

Finish

Non-woven. No pattern repeat, but Vicinity Workstation Screens have a directional grain. Product may vary from samples and batch to batch due to fibre blending and lay-up, which is an inherent feature of this product.

Service

For further information about Vicinity Workstation Screens or any other Autex Acoustics product, please contact your account manager or visit our website.

The information contained in this document is correct to the best of our knowledge at the date of its publication. It is the user's responsibility to determine if this information is suitable for their intended application and to make sure that this document is the most current publication. You can do this by checking our website or contacting your Autex Acoustics account manager.

Care and maintenance

Maintain in accordance with the Care and Maintenance Guide available for this product.

● **New Zealand**
702-718 Rosebank Road,
Private Bag 19988
Avondale 1746, Auckland
T 0800 428 839
T +64 9 828 9179
autexacoustics.co.nz

● **Australia**
285 Swan Street,
Richmond, VIC 3121
T 1800 678 160
T +61 3 9450 6700
autexacoustics.com.au

● **United Kingdom**
Unit J4, Lowfields Way,
Lowfields Business Park,
Elland, West Yorkshire
HX5 9DA
T +44 0 142 241 8899
autexacoustics.co.uk

● **United States**
1630 Dan Kipper Drive,
Riverside, CA 92507
T +1 424 203 1813
autexacoustics.com