



**Autex  
Acoustics®**

Cascade™

Manufacturer's Guarantee

The Cube™ component of Cascade™ Hanging Screens is manufactured by Autex Industries Ltd and Autex Australia Pty Ltd under an ISO 9001 and ISO 14001 certified Quality Environmental Management Systems. The product is guaranteed to be free from manufacturing defects and carries a Manufacturer's Guarantee for a period of no less than ten years to meet all of the performance properties stated within this guarantee.

**Expanding and folding panel patent**

US Patent 10,184,249

**Specification**

**Product name** Cascade  
**Description** 100% polyester lightweight semi-rigid panel

	Imperial
Panel dimensions	47.2" x 94.5"
Thickness	1/2"
Tolerance	(+/- 6%)
Weight	7.54 oz/ft <sup>2</sup>

**Physical description/  
properties**

Boiling point	N/A
Melting point:	250°C   482°F
Vapor pressure:	N/A
Specific gravity:	Polyester 1.38
Flash point:	N/A
Explosive limits:	N/A
Solubility in water	Not soluble
Alkalinity:	pH 7.8
Relative vapor density:	N/A

**Acoustic performance**

Cascade is specifically designed to reduce and control reverberated noise and echo in building interiors. For a copy of the acoustic report please contact your account manager.

Frequency (Hz)	125	250	500	1000	2000	4000	Per unit
● Cascade™ Static 1/2"	0.3	0.6	1.2	2.1	3.1	3.6	1.70
● Cascade™ Folding/Expanding 1/2"	0.4	0.9	1.5	2.7	3.8	4.3	2.25



## Service

For further information about Cascade or any other Autex Acoustics product, please contact your account manager or visit our website.

## Care and maintenance

Maintain in accordance with the Care and Maintenance Guide available for this product.

## Product specifications

### Composition

100% polyester fiber from polyethylene terephthalate (PET). Cascade contains a minimum of 60% previously recycled polyester fiber.

### Suitable applications

Fixed or suspended acoustic partition system.

### Pack contents

1 x Cascade Screen  
1 x Frontier™ Channel  
2 x Ceiling Connectors  
2 x 1 m Wires  
2 x Autex Suspension Sliders

Note: Expanding Screens have double the pack contents.

### Fire rating

Cascade is made from Cube™ as the base material. Cube has been evaluated using the following test methods:

### ISO 9705

Classification: Group 1-S  
Smoke production rate: <5.0m<sup>2</sup>/s  
As required by NZBC C/VM2

### AS ISO 9705

Australian Group Number:  
Group 1  
(SMOGRARC): < 100m<sup>2</sup>/s<sup>2</sup>  
Assessed using methodology AS ISO 9705 in accordance with AS56371:2015 as required by BCA  
Specification C110-4  
FI 4974  
FAR 4055

### BS EN 13501-1

Ceiling applications  
Classification: B-s<sub>2</sub>,d0  
(Cube™ 12 mm)  
Tested using BS EN ISO 11925-2:2020 and BS EN 13823:2020 and classified in accordance with BS EN 13501-1:2018, as required by BS EN 13964:2014.  
EUI-20-000268-B

### BS EN 1021-1

Result: Pass (Cigarette)  
1362214.7

### ASTM E-84-15a

Class A, FS:0 - SD:45  
RJ4479-2

### VOC emissions

Autex Acoustics polyester has been tested for chemical emissions in accordance with ASTM D5116 and is considered a low VOC product.  
VOC concentration:  
0.009 mg/m<sup>3</sup> (7 days)

### Water vapor sorption

ASTM C1104 / C1104M-13a  
Test conditions: 49°C, 95%RH  
Water vapor absorbed and adsorped after 4 days: 0.4% by weight.

### Microbial resistance

ASTM G21-15  
Growth rating: 0 (No growth)  
Cascade does not promote the growth of mold and mildews.

### Color fastness to light

Cascade is suitable for indoor use only. Light fastness is dependent on use and exposure. Cascade has been evaluated to the following standard:  
ISO 105-B02:2014  
Rating: 6 (Highest = 7)

### Color fastness to rubbing

ISO 105-X12:2016  
Dry rating: 4-5 (Highest = 5)  
Wet rating: 4-5 (Highest = 5)

### Pattern repeat

Non-woven. No pattern repeat but product has directional grain. Product may vary from samples and batch to batch due to fiber blending and lay-up, which is an inherent feature of this product.

### Fabric care

Blot spills from fabric quickly. Wipe with a damp cloth. Avoid rubbing and excessive amounts of water as this will affect the finish. Use carpet or upholstery shampoo as directed. Blot with a clean dry cloth after each application of solution.

Custom printed Cascade requires the services of a specialist cleaning company. Refer to the Cascade Care and Maintenance Guide for more information.

## Environmental

Autex Acoustics is committed to best practice through our ISO 14001 certified Environmental Management Systems.

Cascade contains a minimum of 60% previously recycled polyester fiber (from PET bottle-flake). Off-cuts and manufacturing waste are re-used or recycled wherever possible.

Cascade is manufactured from 100% polyester fiber and does not contain formaldehyde binders. Autex Acoustics polyester fiber supports safer indoor air quality and will not become a potential airborne pollutant.

### ● Autex Industries Ltd

702-718 Rosebank Rd  
Private Bag 19988  
Avondale 1746, Auckland  
New Zealand  
Freephone 0800 428 839  
Phone +64 9 828 9179  
Fax +64 9 828 5810

### ● Autex Australia Pty Ltd

166 Bamfield Road  
PO Box 5099  
West Heidelberg, Melbourne  
VIC 3081, Australia  
Freephone 1800 678 160  
Phone +61 3 9457 6700  
Fax +61 3 9457 1020

### ● Autex Acoustics Ltd

Unit J4, Lowfields Way,  
Lowfields Business Park,  
Elland, West Yorkshire  
Hx5 9Da  
United Kingdom  
Phone +44 0 1422418899

### ● Autex Acoustics LLC

1630 Dan Kipper Dr,  
Riverside, CA 92507  
United States of America  
Phone +1 424 203 1813

An ISO 9001, ISO 14001 and ISO 45001 certified company. The brand names and logos mentioned herein are registered or unregistered trademarks either owned or used under license by Autex Industries Limited or other members of the Autex Group. The contents of this document are protected by Copyright 2021 Autex Industries Ltd. All Rights Reserved. It is the user's responsibility to determine if the product and information presented in this document is suitable for the intended application by engaging a suitably qualified consultant. The information contained in this document is correct to the best of our knowledge at the date of its publication. To verify that this document is the most current publication please check our website or contact your Autex account manager.