



**Autex
Acoustics®**

Composition Peel 'N' Stick Tiles®

Manufacturer's Guarantee

Composition® Peel 'n' Stick Tiles are manufactured by Autex Industries Ltd and Autex Australia Pty Ltd under ISO 9001 and ISO 14001 certified Environmental and Quality Management Systems. The product is guaranteed to be free from manufacturing defects, and carries a Manufacturer's Guarantee for a period of no less than ten years to meet all of the performance properties stated within this guarantee.

Specification

Product Name Composition® Peel 'n' Stick Tiles
Description 100% polyester needle punched, thermally bonded wallcovering.

	Imperial
Tile Dimensions	23.6" x 23.6"
Tile Tolerance	(+/-0.02") x (+/-0.02")
Thickness	0.4" - 0.5"
Thickness Tolerance	(+/- 6%)
Weight	5.51 oz/ft2

Physical Description / Properties

Boiling Point	N/A
Melting Point:	482°F
Vapor Pressure:	N/A
Specific Gravity:	Polyester 1.38
Flash point:	N/A
Explosive limits:	N/A
Solubility in water	Not soluble
Alkalinity:	pH 7.8
Relative Vapor Density:	N/A

Acoustic Performance

Composition Peel 'n' Stick Tiles are specifically designed to reduce and control reverberated (echo) noise in building interiors.

Noise Reduction
Coefficient 0.40

Frequency (Hz)	125	250	500	1000	2000	4000	NRC
● Composition Peel 'n' Stick Tiles (0.4" - 0.5")	0.05	0.10	0.25	0.55	0.80	0.95	0.40



Service

For further information about Composition Peel 'n' Stick Tiles or any other Autex product, please contact your Autex account manager or visit our website.

Care and Maintenance

Maintain in accordance with the Care and Maintenance Guide available for this product.

Product Specifications

Composition

100% polyester fiber from polyethylene terephthalate (PET). Composition Peel 'n' Stick Tiles contain a minimum of 60% recycled polyester fiber.

Suitable Applications

Pinboard and acoustic wallcovering. Accepts pins and staples.

Fire Ratings

Composition Peel 'n' Stick Tiles are a product made from Autex Composition as the base material. Composition has been evaluated using the following test methods:

ISO 9705: 1993

Classification: Group 1-S
Smoke Production Rate:
<5.0m²/s
As required by NZBC C/VM2

AS ISO 9705 - 2003

Classification: Group 1
(SMOGR_{arc}): <100m²/s²
Assessed using methodology
AS ISO 9705:2003
in accordance with AS 56371:2015, as required by
BCA Specification C110-4
FI 4894
FAR 4055

EN13501-1:2007

B - s1, d0
Report 189053

ASTM E84 - 14

Class A, FS:5 - SD:25
RJ3297

Thermal Performance

R0.22 (@15°C)

VOC Emissions

Autex polyester has been tested for chemical emissions in accordance with ASTM D5116 and is considered a low VOC product. VOC concentration: 0.009 mg/m³ (7 days)

Microbial Resistance

ASTM G21-15
Growth Rating: 0 (No growth)
Composition Peel 'n' Stick Tiles do not promote the growth of molds and mildew.

Impact Resistance

ISO 7892:1988

Hard Body Impact

There is no surface damage or penetration to Composition Peel 'n' Stick Tiles when subjected to hard body impacts. A small indentation might be observed when subjected to an impact equivalent to the impact of a 0.5kg object dropped from a 0.5-m height. When adhered to 10mm plasterboard, the system can resist a 9-joule impact, and no further indentations are observed. This is equivalent to the impact of a 0.5kg object dropped from a 2m height.

Soft Body Impact

There is no surface damage or penetration to Composition Peel 'n' Stick Tiles when subjected to soft body impacts. When adhered to 10mm plasterboard,

the system can resist a 70-joule impact. This is equivalent to the impact of a 50-kg object dropped from a 150mm height.

Color Fastness to light

Composition Peel 'n' Stick Tiles are suitable for indoor use only. Light fastness is dependent on use and exposure. Composition Peel 'n' Stick Tiles have been evaluated to the following standard: ISO 105-B02:2014
Rating: 6 (Highest = 7)

Acoustic Performance

Autex have researched the acoustic performance of Autex Composition when covered in paper (e.g. children's artwork) and found that it helps achieve a more balanced acoustic environment. In some cases, covering Composition with unlaminated paper can have a positive effect on the acoustic performance of the wall. For more information on this please contact your Autex account manager.

Color Fastness to Rubbing

ISO 105-X12:2016
Dry Rating: 4-5 (Highest = 5)
Wet Rating: 4-5 (Highest = 5)

Pattern Repeat

Non-woven. No pattern repeat, but product has directional grain. Product may vary from samples

and batch to batch due to fibre blending and lay-up, which is an inherent feature of this product.

Finish

Non-woven. No pattern repeat, but Composition Peel 'n' Stick Tiles have a directional grain. Product may vary from samples and batch to batch due to fiber blending and lay-up, which is an inherent feature of this product.

Use of Hook Fasteners

Although the product surface is receptive to hook fasteners, repeated fastening and unfastening may result in wear on the product surface finish.

This is not a product fault, but an inherent nature of non-woven textiles. We recommend low-profile, micro, or thin hook fasteners (max. 0.5mm) as these are found to provide minimal wear on the product surface.

Do not use high-profile or heavy-duty hook fasteners as they may result in visible wear in the product surface finish after repeated attachments. For further information and recommendations on suitable hook fasteners, please contact your Autex account manager.



Environmental

Autex is committed to best practice through our ISO 9001 and ISO 14001 certified Quality and Environmental Management Systems.

Autex Composition Peel 'n' Stick Tiles contain a minimum of 60% previously recycled polyester fibre (from PET bottle-flake).

Off-cuts and manufacturing waste are re-used or recycled wherever possible.

Autex Composition Peel 'n' Stick Tiles are manufactured from 100% polyester fibres and do not contain formaldehyde binders. Autex polyester fibres support safer indoor air quality and will not become a potential airborne pollutant.

● Autex Industries Ltd

702-718 Rosebank Rd
Private Bag 19988
Avondale 1746, Auckland
New Zealand
Freephone 0800 428 839
Phone +64 9 828 9179
Fax +64 9 828 5810

● Autex Australia Pty Ltd

166 Bamfield Road
PO Box 5099
West Heidelberg, Melbourne
VIC 3081, Australia
Freephone 1800 678 160
Phone +61 3 9457 6700
Fax +61 3 9457 1020

● Autex Acoustics Ltd

Unit J4, Lowfields Way,
Lowfields Business Park,
Elland, West Yorkshire
Hx5 9Da
United Kingdom
Phone +44 0 1422418899

● Autex Acoustics LLC

19350 Van Ness Avenue
Torrance, CA 90501
United States of America
Phone +1 424 203 1813

An ISO 9001, ISO 14001 and ISO 45001 certified company. The brand names and logos mentioned herein are registered or unregistered trademarks either owned or used under license by Autex Industries Limited or other members of the Autex Group. The contents of this document are protected by Copyright 2021 Autex Industries Ltd. All Rights Reserved. It is the user's responsibility to determine if the product and information presented in this document is suitable for the intended application by engaging a suitably qualified consultant. The information contained in this document is correct to the best of our knowledge at the date of its publication. To verify that this document is the most current publication please check our website or contact your Autex account manager.