



Cube™ is manufactured by Autex Industries Ltd and Autex Australia Pty Ltd under an ISO 9001 certified Quality Management System. The product is guaranteed to be free from manufacturing defects and carries a Manufacturer's Guarantee for a period of no less than ten years to meet all of the performance properties stated within this guarantee.

**Specification**

**Product Name** Cube™  
**Description** 100% polyester lightweight semi-rigid panel

	Metric		Imperial	
Panel Dimensions	1220mm x 2440mm		4' x 8'	
Tolerance	(±5mm/-0mm) x (±10mm/-0mm)		(±0.20") x (0.40")	
Thickness	12mm	24mm	1/2"	1"
Tolerance	(±/- 6%)	(±/- 6%)	(±/- 6%)	(±/- 6%)
Weight	2400gsm	3600gsm	7.86oz/ft2	12oz/ft2
Density	192kg/m3			

**Physical Description /  
Properties**

Boiling Point	N/A
Melting Point:	250°C   482°F
Vapour Pressure:	N/A
Specific Gravity:	Polyester 1.38
Flash point:	N/Aw
Explosive limits:	N/A
Solubility in water	Not soluble
Alkalinity:	pH 7.8
Relative Vapour Density:	N/A

**Acoustic Performance**

Cube™ is specifically designed to reduce and control reverberated (echo) noise in building interiors. Minimum Noise Reduction Coefficient 0.45

Frequency (Hz)	125	250	500	1000	2000	4000	NRC
● 12mm Cube	0.05	0.10	0.30	0.65	0.90	0.95	0.45
● 12mm Cube (with 25mm air gap)	0.05	0.30	0.60	0.95	0.95	0.85	0.70
● 24mm Cube	0.05	0.20	0.60	0.90	1.00	1.00	0.70
● 24mm Cube (with 25mm air gap)	0.15	0.40	0.85	0.95	0.95	0.95	0.80



## Service

For further information about Cube™ or any other Autex product, please contact your Autex Account Manager or visit our website. Cube™ is a trademark of Autex Industries Limited and Autex Pty.

## Care and Maintenance

Maintain in accordance with the Care and Maintenance Guide available for this product.

## Product Specifications

### Composition

100% Polyester Fibre from polyethylene terephthalate (PET). Cube contains a minimum of 60% previously recycled polyester fibre.

### Suitable applications

Pinboards, partitions, wallcovering with acoustic properties. Accepts pins and staples.

### Colour Fastness To Light

Cube is suitable for indoor use only. Light fastness is dependent on use and exposure. Cube has been evaluated to the following standard:

ISO 105-B02:2014

Rating: 6 (Highest = 7)

### Thermal Performance

Cube™ 12mm R0.41 (@15°C)  
Cube™ 24mm R0.82 (@15°C)

### Fire Ratings

(Conducted on 12mm Cube™)

### ISO 9705: 1993

Classification – Group 1-S  
Smoke Production Rate – <5.0m<sup>2</sup>/s

As required by NZBC C/VM2

### AS ISO 9705 - 2003

Classification – Group 1 (SMOGR<sub>Arc</sub>) – <100m<sup>2</sup>/s<sup>2</sup>  
As required by BCA C1.10  
FI 4974 dated 16th September, 2012

### BS EN 13501-1:2018

Classification: B-s2,d0 (Cube™ 1/2")  
Tested using BS EN ISO 11925-2:2020 and BS EN 13823:2020 and classified in accordance with BS EN 13501-1:2018, as required by BS EN 15102:2007 + A1:2011.  
EUI-20-000268-A

### ASTM E-84-14

Class A, FS:0 – SD:45  
R14479-2

### VOC Emissions

Autex polyester has been tested for chemical emissions in accordance with ASTM D5116 and is considered as a low VOC product.

VOC concentration:  
0.009 mg/m<sup>3</sup> (7 days)

### Finish

Non-woven. No pattern repeat but Cube™ has a directional grain. Product may vary from samples and batch to batch due to fibre blending and lay-up which is an inherent feature of this product.

### Moisture Absorption

Polyester fibre when exposed to an atmosphere of 50°C at 90% relative humidity for four days showed moisture absorption of less than 0.03% by weight.

Polyester is not affected by moisture, mould or mildew and will not rot or deteriorate in intended use situations.

### Pattern Repeat

Non-woven. No pattern repeat but product has directional grain. Product may vary from samples and batch to batch due to fibre blending and lay-up which is an inherent feature of this product.

### Fabric Care

Refer to Cleaning Guide  
[www.autexindustries.com](http://www.autexindustries.com)

### Impact Resistance ISO 7892:1988

### Hard Body Impact

There is no surface damage or penetration to Cube when subjected to hard body impacts. When adhered to 10mm plasterboard, the system can resist a 9-joule impact. This is equivalent to the impact of a 0.5kg object dropped from a 2m height. A small indentation might be observed

when subjected to an impact equivalent to the impact of a 0.5kg object dropped from a 0.5-m height.

### Soft Body Impact

There is no surface damage or penetration to Cube when subjected to soft body impacts. When adhered to 10mm plasterboard, the system can resist a 70-joule impact. This is equivalent to the impact of a 50-kg object dropped from a 150mm height.

## Environmental

Autex Cube is manufactured using 100% polyester fibre and contains a minimum of 50% post consumer recycled content (i.e. PET plastic bottles).

Autex Cube is Global GreenTag GreenRate Level A certified and can be used to contribute to Green Star NZ accreditation. Autex Cube™ is also Declare certified to be Red-List Free and can be used in Living Building Challenge projects.

All Autex product declarations are independently verified under the auditing process of our ISO 14001 Environmental Management System. For more information, please contact your Autex Account Manager, or visit our website [www.autexindustries.com](http://www.autexindustries.com)

### ● Autex Industries Ltd

702-718 Rosebank Rd  
Private Bag 19988  
Avondale 1746, Auckland  
New Zealand  
Freephone 0800 428 839  
Phone +64 9 828 9179  
Fax +64 9 828 5810

### ● Autex Australia Pty Ltd

166 Bamfield Road  
PO Box 5099  
West Heidelberg, Melbourne  
VIC 3081, Australia  
Freephone 1800 678 160  
Phone +61 3 9457 6700  
Fax +61 3 9457 1020

### ● Autex Acoustics Ltd

Unit J4, Lowfields Way,  
Lowfields Business Park,  
Elland, West Yorkshire  
Hx5 9Da  
United Kingdom  
Phone +44 0 1422418899

### ● Autex Acoustics LLC

1630 Dan Kipper Dr,  
Riverside, CA 92507  
United States of America  
Phone +1 424 203 1813