



## Product Overview

This document is designed to guide you through the Print design process. Print is a customisation option that offers complete design freedom. Achieve natural high-end finishes without the cost, weight, and rigidity of materials such as timber, tile, and marble. Print solid colour, intricate patterns, and contemporary designs to create striking acoustic art pieces. Easy to colour match, we can print to your selected CMYK or Pantone palette ensuring colour continuity throughout your design. Print is available on Cube™ 12mm/24mm, Frontier™, Cascade™, Lattice™, Vicinity™, Horizon™, and Quietspace® Panel 25mm. To specify Print for your project you will need to supply the data sheet or brochure of the selected product as well as the Print Manufacturer's Guarantee.

---

## For more information on Print please refer to the following documents:

- Print Lookbook
  - Print Install Instructions
  - Print Manufacturer's Guarantee
  - Cube Data Sheet
- 

## Features and Benefits

- Safe, water-based, UV cured vegetable ink
  - Low VOC
  - No MOQ's and short lead times (initially 2 weeks)
  - Available across a range of high-performance acoustic treatments
  - Endless customisation options
  - Crisp colours and lines
  - Made in New Zealand
- 

## How to specify Print

- Select the acoustic product you want e.g. Cube™ 12mm/24mm, Frontier™, Cascade™, Lattice™, Vicinity™, Horizon™, and Quietspace® Panel 25mm.
- Choose from our suggestions, or supply a bespoke design (please refer to the Print Guide for suggestions).
- For panel/product sizes, refer to the relevant product datasheet.
- For patterns/vectors, please supply as follows:
  - File format: EPS or Ai (Illustrator file)
  - Colour mode: CMYK
  - File setup: Supply at full 1:1 scale with dimensions noted. Pattern repeats are recommended to be seamless.
  - For prints at or below 1200 x 2400mm, a 10mm overprint bleed is required for cutting.
  - For prints over 1200x2400mm or across multiple panels please get in touch with your account manager.



## How to specify Print

- For images, please supply as follows:
  - File format: Jpeg or PSD (Photoshop file)
  - Colour mode: CMYK for PSD, RGB for JPEG
  - File setup: Images to be supplied at full 1:1 scale, resolution to be minimum 150 DPI, ideal 300DPI. Artwork to be supplied with dimensions noted. For prints at or below 1200x2400mm, a 10mm overprint bleed is required for cutting. For prints over 1200x2400mm or across multiple panels please get in touch with your account manager.
  - When supplying an image for Print, you need permission from the creator of the content to use it in your intended way. Please make sure you have all the correct permissions rights in writing before supplying the image. Alternatively, you can consider having artwork created specifically for your particular project.

If you have any questions about specifying Print, please contact your Autex account manager. Your account manager will liaise with our in-house design team to create the acoustic products required for your project.

---

### ● Autex Industries Ltd

702-718 Rosebank Rd  
Private Bag 19988  
Avondale 1746, Auckland  
New Zealand  
Freephone 0800 428 839  
Phone +64 9 828 9179  
Fax +64 9 828 5810

### ● Autex Australia Pty Ltd

166 Bamfield Road  
PO Box 5099  
West Heidelberg, Melbourne  
VIC 3081, Australia  
Freephone 1800 678 160  
Phone +61 3 9457 6700  
Fax +61 3 9457 1020

### ● Autex Acoustics Ltd

Unit J4, Lowfields Way,  
Lowfields Business Park,  
Elland, West Yorkshire  
Hx5 9Da  
United Kingdom  
Phone +44 0 1422418899

### ● Autex Acoustics LLC

1630 Dan Kipper Dr,  
Riverside, CA 92507  
United States of America  
Phone +1 424 203 1813

An ISO 9001, ISO 14001 and ISO 45001 certified company. The brand names and logos mentioned herein are registered or unregistered trademarks either owned or used under license by Autex Industries Limited or other members of the Autex Group. The contents of this document are protected by Copyright 2021 Autex Industries Ltd. All Rights Reserved. It is the user's responsibility to determine if the product and information presented in this document is suitable for the intended application by engaging a suitably qualified consultant. The information contained in this document is correct to the best of our knowledge at the date of its publication. To verify that this document is the most current publication please check our website or contact your Autex account manager.