



Print is suitable as a decorative finish for acoustic products in retail, hospitality, and commercial interiors. When selecting Print, please contact your Autex account manager to discuss applications.

Applications

Print can be added to the below products:

- Cube™ 12mm / 24mm
- Frontier™ Fins/Raft
- Quietspace® panel 25mm
- Vicinity™
- Cascade™
- Lattice™
- Horizon™

Product Specifications

Suitable Applications

Suitable for use as acoustic and decorative treatments where contact with the product will be minimal. If you have any concerns about the install location, please contact your account manager.

Acoustic Performance

Print has been tested and found to have no impact on the acoustic performance of Autex Interior Acoustics products. Please contact your Autex account manager for further information if required.

Pinnable

Printed Cube is pinnable. However, please be aware that the surface is not self-healing, and the backing panel colour may be visible when pinning.

Impact Resistance

Print may show surface damage when subjected to impacts. We would advise against using Print in areas where there is likely to be contact with the product.

Fire Ratings

Testing results for 25mm Quietspace Panel & 12mm Cube:

ISO 9705: 1993

Classification: Group 1-S
Smoke Production Rate: <5.0m²/s

As required by NZBC C/VM2

AS ISO 9705 - 2003

Classification: Group 1 (SMOGR_{Arc}): <100m²/s²
Assessed using methodology AS ISO 9705:2003 in accordance with AS 5637:2015, as required by BCA Specification C1.10-4. FAR 4055

EN13501-1:2007+A1:2009

(12mm Cube)
B - s₂, d₂
WF336911

EN13501-1:2007

(25mm Quietspace Panel)
B - s₂, d₀
Report 185157

ASTM E-84-15a

(1/2" Cube)
Class A, FS:0 - SD:45
RJ4479

ASTM E-84-14:

(1" Quietspace Panel)
Class A FS:0 - SD:10
Report RJ3297

VOC Emissions

Print has been tested for chemical emissions in accordance with ASTM D5116 and is considered a low VOC and low formaldehyde emissions product. VOC emissions: 0.019 mg/m³
Formaldehyde emissions: <0.005 mg/m³

Colour Fastness To Light

Print is suitable for indoor use only. Light fastness is dependent on use and exposure. Print has been evaluated to the following standard: ISO 105-B02:2014
Rating: 6 (Highest = 7)

Light Refelctance Value (LRV) Solid Colours

Print can be supplied in several custom color options. When selecting Print, a sample can be provided and tested for LRV. Please contact your Autex account manager at the start of your project to arrange a test.

Fabric Care

Avoid contact with the Print surface. Do not clean the surface with any liquid, including water. Consult a specialist cleaning company for cleaning if required.

Finish

The acoustic product colour may vary from samples and between each product batch. This is due to the inherent nature of the textile. This will not affect the colour of the Print.



Service

For further information about Print or any other Autex product, please contact your Autex account manager or visit our website. The information contained in this document is correct to the best of our knowledge at the date of its publication. It is the user's responsibility to determine if this information is suitable for their intended application and to make sure that this document is the most current publication. You can do this by checking our website or contacting your Autex account manager.

Care and Maintenance

Maintain in accordance with the Care and Maintenance Guide available for this product.

- **Autex Industries Ltd**

702-718 Rosebank Rd
Private Bag 19988
Avondale 1746, Auckland
New Zealand
Freephone 0800 428 839
Phone +64 9 828 9179
Fax +64 9 828 5810

- **Autex Australia Pty Ltd**

166 Bamfield Road
PO Box 5099
West Heidelberg, Melbourne
VIC 3081, Australia
Freephone 1800 678 160
Phone +61 3 9457 6700
Fax +61 3 9457 1020

- **Autex Acoustics Ltd**

Unit J4, Lowfields Way,
Lowfields Business Park,
Elland, West Yorkshire
Hx5 9Da
United Kingdom
Phone +44 0 1422418899

- **Autex Acoustics LLC**

1630 Dan Kipper Dr,
Riverside, CA 92507
United States of America
Phone +1 424 203 1813