



Available across a selection of our leading acoustic solutions, our Surface Finishes range offers a collection of modern timber, texture, pattern, and stone looks—hand selected to help you achieve natural, high-end aesthetics without the cost, weight, or rigidity of traditional materials. Surface Finishes are suitable as a decorative finish for acoustic products in retail, hospitality, and commercial interiors. When selecting Surface Finishes, please contact your account manager to discuss applications.

Applications

Surface Finishes can be added to the below products:

- Cube™ 1/2" / 1"
- Frontier™ Acoustic Fins/Raft
- Quietspace® Panel 1"
- Horizon™

Product specifications

Suitable applications

Autex Acoustics recommends specification of Surface Finishes in non-contact areas. For applications where contact is likely to occur, Autex Acoustics recommends our standard Cube™ or Quietspace® Panel range.

Acoustic performance

Surface Finishes have been tested and found to have no impact on the acoustic performance of Autex Acoustics products. Please contact your account manager for further information if required.

Impact resistance

Surface Finishes may show surface damage when subjected to impacts. We would advise against using Surface Finishes in areas where there is likely to be contact with the product.

Fire ratings

Testing results for 1" Quietspace Panel and 1/2" Cube:

ISO 9705: 1993

Classification: Group 1-S
Smoke production rate: <5.0m2/s
As required by NZBC C/VM2

AS ISO 9705 - 2003

Classification: Group 1 (SMOGRArc): <100m2/s2
Assessed using methodology AS ISO 9705:2003 in accordance with AS 56371:2015, as required by BCA Specification C110-4, FAR 4055

BS EN 13501-1:2018

Wall applications
Classification: B-s2,d0 (Cube™ 12 mm)
Tested using BS EN ISO 11925-2:2020 and BS EN 13823:2020 and classified in accordance with BS EN 13501-1:2018, as required by BS EN 15102:2007 A1:2011, EUI-20-000268-A

Ceiling applications

Classification: B-s2,d0 (Cube™ 12 mm)
Tested using BS EN ISO 11925-2:2020 and BS EN 13823:2020 and classified in accordance with BS EN 13501-1:2018, as required by BS EN 13964:2014, EUI-20-000268-B

ASTM E-84-15a

(1/2" Cube)
Class A, FS:0 - SD:45
RJ4479

ASTM E-84-14:

(1" Quietspace Panel)
Class A FS:0 - SD:10
Report RJ3297

VOC emissions

Surface Finishes has been tested for chemical emissions in accordance with ASTM D5116 and is considered a low VOC and low formaldehyde emissions product.
VOC emissions: 0.019 mg/m3
Formaldehyde emissions: <0.005 mg/m3

Color fastness to light

Surface Finishes are suitable for indoor use only. Light fastness is dependent on use and exposure. Surface Finishes has been evaluated to the following standard:
ISO 105-B02:2014
Rating: 6 (Highest = 7)

Light Reflectance Value (LRV) solid colors

Surface Finishes can be supplied in several custom color options. When selecting Surface Finishes, a sample can be provided and tested for LRV.

Please contact your account manager at the start of your project to arrange a test.

Fabric care

Avoid contact with the printed surface. Do not clean the surface with any liquid, including water. Consult a specialist cleaning company for cleaning if required.

Finish

The acoustic product color may vary from samples and between each product batch. This is due to the inherent nature of the textile. This will not affect the colour of the Surface Finishes.



Service

For further information about Surface Finishes or any other Autex Acoustics product, please contact your account manager or visit our website. The information contained in this document is correct to the best of our knowledge at the date of its publication. It is the user's responsibility to determine if this information is suitable for their intended application and to make sure that this document is the most current publication. You can do this by checking our website or contacting your account manager.

Care and maintenance

Maintain in accordance with the Care and Maintenance Guide available for this product.

● Autex Industries Ltd

702-718 Rosebank Rd
Private Bag 19988
Avondale 1746, Auckland
New Zealand
Freephone 0800 428 839
Phone +64 9 828 9179
Fax +64 9 828 5810

● Autex Australia Pty Ltd

166 Bamfield Road
PO Box 5099
West Heidelberg, Melbourne
VIC 3081, Australia
Freephone 1800 678 160
Phone +61 3 9457 6700
Fax +61 3 9457 1020

● Autex Acoustics Ltd

Unit J4, Lowfields Way,
Lowfields Business Park,
Elland, West Yorkshire
Hx5 9Da
United Kingdom
Phone +44 0 1422418899

● Autex Acoustics LLC

1630 Dan Kipper Dr,
Riverside, CA 92507
United States of America
Phone +1 424 203 1813

An ISO 9001, ISO 14001 and ISO 45001 certified company. The brand names and logos mentioned herein are registered or unregistered trademarks either owned or used under license by Autex Industries Limited or other members of the Autex Group. The contents of this document are protected by Copyright 2021 Autex Industries Ltd. All Rights Reserved. It is the user's responsibility to determine if the product and information presented in this document is suitable for the intended application by engaging a suitably qualified consultant. The information contained in this document is correct to the best of our knowledge at the date of its publication. To verify that this document is the most current publication please check our website or contact your Autex account manager.