



THERMAL PADS

GreenStuf® Thermal Pads are 100% polyester semi-rigid thermal insulation segments pre-cut to fit common timber- framed walls, ceilings and mid-floor joist spacings.

APPLICATIONS

GreenStuf Thermal Pads are designed for the thermal insulation of timber framed buildings in accordance with New Zealand Building Code (NZBC) H1 Energy Efficiency requirements. GreenStuf Thermal Pads can be used in ceilings, internal and external walls and mid-floor cavities. To ensure Building Code compliance, architects and building designers are advised to consult an engineer or the relevant NZ standards before specifying thermal and acoustic insulation products. For information and assistance please contact your Autex account manager.

TECHNICAL

NZBC Compliance: When installed in accordance with the manufacturer's instructions, GreenStuf insulation will satisfy the 50 year durability clause NZBC B2.3.1 (a). GreenStuf meets the relevant clauses of NZBC E3 Internal Moisture, F2 Hazardous Building Materials, and will contribute to meeting H1 Energy Efficiency.

Fire Regulations: GreenStuf insulation may not be suitable for all applications, as stipulated in the NZBC. Please consult a fire engineer when specifying GreenStuf insulation or contact your Autex account manager for further information.

Acoustic Performance: GreenStuf insulation will assist sound reduction by reducing the resonating noise inside the construction cavity. Typical improvement in sound transmission loss through walls with the use of GreenStuf R2.0 Wall insulation is an increase of 5-6 STC points.

Hazardous Building Materials: GreenStuf is non-hazardous.

Durability: GreenStuf has a 50 Year Durability Warranty.

Moisture: GreenStuf is not affected by moisture. Exposure to an atmosphere of 50°C at 90% relative humidity for four days showed moisture absorption by weight of less than 0.03%.



Declare.



Fire ratings:

ISO 9705: 1993

Classification: Group 1-5

Smoke Production Rate: <5.0m²/s

As required by NZBC C/VM2

FAR 4045-2 issued 8th October, 2013

AS1530.3

Ignitability Index (0-20) 0

Heat Evolved Index (0-10) 0

Spread of Flame Index (0-10) 0

Smoke Developed Index (0-10) 3

APL Report 98055 (Test conducted on GreenStuf Thermal Insulation)

IEC 60695-11-5 (Downlight Fire Test Standard)

GreenStuf has been tested and assessed as complying with IEC 60695-11-5 Needle-flame Test.

VOC Emission Safe:

VOC concentration: 0.01 mg/m³ (7 days).

GECA/GreenGuard Limit: 0.25 mg/m³ (7 days).

Cetec Pty Ltd (Report: RCV080408)

PRODUCT (R-value)		NOMINAL THICKNESS (mm)	PACK SIZE	PRODUCT WEIGHT (GSM)	DENSITY (kg/m ³)	m ² /PACK
R2.0 Wall Retrofit		70mm	560mm x 1160mm x 10 pads per bale	3,600gsm	51.4kg/m ³	6.50m ²
R2.0 Wall	✓	90mm	560mm x 1160mm x 18 pads per bale	1,500gsm	16.7kg/m ³	11.69m ²
R2.0 Wall		90mm	360mm x 1160mm x 20 pads per bale	1,500gsm	16.7kg/m ³	8.35m ²
R2.2 Wall	✓	90mm	560mm x 1160mm x 18 pads per bale	1,950gsm	21.7kg/m ³	11.69m ²
R2.2 Wall		90mm	360mm x 1160mm x 18 pads per bale	1,950gsm	21.7kg/m ³	7.52m ²
R2.5 Wall	✓	90mm	560mm x 1160mm x 10 pads per bale	3,250gsm	36.1kg/m ³	6.50m ²
R2.5 Wall		90mm	360mm x 1160mm x 12 pads per bale	3,250gsm	36.1kg/m ³	5.01m ²
R2.9 Ceiling	✓	175mm	430mm x 1220mm x 13 pads per bale	1,550gsm	8.9kg/m ³	6.82m ²
R3.2 Ceiling	✓	180mm	430mm x 1220mm x 13 pads per bale	1,700gsm	9.4kg/m ³	6.82m ²
R3.4 Ceiling	✓	190mm	430mm x 1220mm x 10 pads per bale	1,950gsm	10.3kg/m ³	5.25m ²

Non-Corrosive: GreenStuf polyester is considered non-corrosive based on AS/NZS 4859.1 Standard for insulation

Non-Toxic, Non-Allergenic, Non-Irritant: There are no known hazards with the use or handling of GreenStuf polyester.

Vermin: GreenStuf is naturally resistant to insect and vermin attack.

Installation: Autex recommends that all thermal and acoustic insulation be installed in accordance with the manufacturer's instructions (included on each GreenStuf Thermal Pads pack) and NZS 4246 Energy Efficiency - Installing Bulk Insulation in Residential Buildings.

With a drained cavity wall construction and stud spacings greater than 450mm, NZBC E2/AS1, 9.1.8.5 Wall Framing behind Cavities, requires stud straps to prevent insulation bulging into the cavity. Straps must be run at 300mm centres over the wall underlay.

When retrofitting in exterior walls (without wall underlay) with direct-fixed claddings, use semi-rigid insulation that is at least 20mm thinner than the framing width (e.g. for walls with 90mm framing, the insulation shall be no thicker than 70mm).

MSDS: Material Safety Data Sheets (MSDS) are available on request from your Autex account manager or can be downloaded from our website: www.greenstuf.co.nz

Specification & Substitution: Autex specification documents are available through Masterspec or can be downloaded from our website (www.greenstuf.co.nz). Substitution of any products in NZBC compliant systems should not be accepted and we recommend this be made clear in all specification and tender documents.

ISO Standards: Autex is committed to Quality and Environmental best practice through our ISO 9001 & ISO 14001 certified Quality and Environmental Management Systems.

Take Back Programme: GreenStuf is recyclable. Autex will gladly recycle used, uncontaminated GreenStuf insulation to help keep it out of landfills. For more information on recycling GreenStuf contact Autex on freephone 0800 428 839.

Packaging Recycling: GreenStuf packaging is recyclable LDPE 4. Please refer to your local recycling centres for drop off and collection services.

Environmental: All GreenStuf products are manufactured using 100% polyester fibre and contain a minimum of 50% previously recycled fibre (from PET plastic). GreenStuf products are manufactured under Autex's Zero Waste Programme where all manufacturing waste is recycled back into the production process.

GreenStuf products are Global GreenTag GreenRate Level A certified and can be used to contribute to Green Star and Homestar accreditation.

GreenStuf is also Declare certified to be Red List chemical free and can be used in Living Building Challenge projects. For more information, please contact your Autex account manager, or visit our website www.greenstuf.co.nz

GreenStuf is manufactured in New Zealand by Autex Insulation, a division of Autex Industries Limited. Autex retains the right to change products and specifications without prior notice. If a specification is critical to end use situation please discuss your requirements with your Autex account manager.

GreenStuf® is a registered trademark of Autex Industries.

GS_NZ_DS_Thermal-Pads-Data-Sheet_Mar19_CT

AUTEX



Insulation

Autex Industries Ltd
702 - 718 Rosebank Rd
Private Bag 19988,
Avondale 1746, Auckland
New Zealand
Phone **+64 9 828 9179**
Fax **+64 9 828 5810**
Freephone 0800 428 839
www.autex.co.nz

ISO 9001 AND ISO 14001 CERTIFIED