



# INTERIOR ACOUSTICS

# PRINT

## MANUFACTURER'S GUARANTEE

### LIGHT REFLECTANCE VALUE (LRV) - SOLID COLOURS

Print can be supplied in several custom colour options. When selecting Print, a sample can be provided and tested for LRV. Please contact your Autex account manager at the start of your project to arrange a test.

### APPLICATIONS

Print is suitable as a decorative finish for acoustic products in retail, hospitality, and commercial interiors. When selecting Print, please contact your Autex account manager to discuss applications.

Print can be added to the below products:

Cube™ 12/24mm  
Frontier™ Fins/Raft  
Quietspace® 25mm panel  
Vicinity™  
Cascade™  
Lattice™  
Horizon™

### SUITABLE APPLICATIONS

Suitable for use as acoustic and decorative treatments where contact with the product will be minimal. If you have any concerns about the install location, please contact your account manager.

### INSTALLATION

Install as per Print recommendations. Install instructions for Print should be used in conjunction with the install instructions for the specified Autex product.

### ACOUSTIC PERFORMANCE

Print has been tested and found to have no impact on the acoustic performance of Autex Interior Acoustics products. Please contact your Autex account manager for further information if required.

### FIRE RATINGS

Testing results for 25mm Quietspace® Panel & 12mm Cube:

#### ISO 9705: 1993

Classification: Group 1-S  
Smoke Production Rate: <5.0m<sup>2</sup>/s  
As required by NZBC C/VM2

#### AS ISO 9705 - 2003

Classification: Group 1  
(SMOGR<sub>Arc</sub>): <100m<sup>2</sup>/s<sup>2</sup>  
Assessed using methodology AS ISO 9705:2003 in accordance with AS 5637.1:2015, as required by BCA Specification C1.10-4.  
FAR 4055

#### EN13501-1:2007+A1:2009 (12mm Cube™)

B - s2, d2  
WF336911

#### EN13501-1:2007 (25mm Quietspace® Panel)

B - s2, d0  
Report 185157

#### ASTM E-84-15a (1/2" Cube™)

Class A, FS:0 - SD:45  
RJ4479

#### ASTM E-84-14: (1" Quietspace® Panel)

Class A FS:0 - SD:10  
Report RJ3297

### VOC EMISSIONS

Print has been tested for chemical emissions in accordance with ASTM D5116 and is considered a low VOC and low formaldehyde emissions product.

VOC emissions: 0.019 mg/m<sup>3</sup>

Formaldehyde emissions: <0.005 mg/m<sup>3</sup>

### COLOUR FASTNESS TO LIGHT

Print is suitable for indoor use only.

Light fastness is dependent on use and exposure. Print has been evaluated to the following standard:

ISO 105-B02:2014

Rating: 6 (Highest = 7)



## PINNABLE

Printed Cube is pinnable. Please be aware when pinning through the surface as the backing panel colour may be visible, and it is not self-healing.

## IMPACT RESISTANCE

Print may show surface damage when subjected to soft body impacts. We would advise against using Print in areas where there is likely to be contact with the product.

## FABRIC CARE

Avoid contact with the Print surface. Do not clean the surface with any liquid, including water. Consult a specialist cleaning company for cleaning if required.

## FINISH

The acoustic product colour may vary from samples and between each product batch. This is due to the inherent nature of the textile. This will not affect the colour of the Print.

## SERVICE

For further information about Print or any other Autex product, please contact your Autex account manager or visit our website. The information contained in this document is correct to the best of our knowledge at the date of its publication. It is the user's responsibility to determine if this information is suitable for their intended application and to make sure that this document is the most current publication. You can do this by checking our website or contacting your Autex account manager.

**AUTEX**   
Interior Acoustics

[www.autexglobal.com](http://www.autexglobal.com)

AN ISO 9001 AND ISO 14001 CERTIFIED COMPANY

**Autex Industries Ltd**  
702-718 Rosebank Rd,  
Private Bag 19988,  
Avondale 1746, Auckland,  
New Zealand  
Freephone **0800 428 839**  
Phone **+64 9 828 9179**  
Fax **+64 9 828 5810**

**Autex Australia Pty Ltd**  
166 Bamfield Road,  
PO Box 5099,  
West Heidelberg, Melbourne,  
VIC 3081, Australia  
Freephone **1800 678 160**  
Phone **+61 3 9457 6700**  
Fax **+61 3 9457 1020**

**Autex Acoustics Ltd**  
Unit J4, Lowfields Way,  
Lowfields Business Park,  
Elland, West Yorkshire,  
Hx5 9Da,  
United Kingdom  
Phone **+44 0 1422 418899**

**Autex Acoustics LLC**  
19350 Van Ness Avenue  
Torrance, CA 90501  
United States of America  
Phone **+1 424 203 1813**

The brand names and logos mentioned herein are registered or unregistered trademarks either owned or used under license by Autex Industries Limited or other members of the Autex Group. The contents of this document are protected by Copyright 2020 Autex Industries Ltd. All Rights Reserved.

It is the user's responsibility to determine if the product and information presented in this document is suitable for the intended application by engaging a suitably qualified consultant. The information contained in this document is correct to the best of our knowledge at the date of its publication. To verify that this document is the most current publication please check our website or contact your Autex account manager.