



INTERIOR ACOUSTICS

FRONTIER™ ACOUSTIC RAFT

MANUFACTURER'S GUARANTEE

Pat. Pending NZ 727634, AU 2016273959

Frontier™ Acoustic Raft is manufactured by Autex Industries Ltd and Autex Australia Pty Ltd under an ISO 9001 certified Quality Management System. The product is guaranteed to be free from manufacturing defects and carries a Manufacturer's Guarantee for a period of no less than ten years to meet all of the performance properties stated within this guarantee.

Product Name Frontier™ Acoustic Raft
Description 100% polyester complete modular acoustic fins

AUTEX	METRIC
Size	Length: 2400mm
Thickness	12mm
Tolerance	(+/- 6%)

COMPOSITION

100% Polyester Fibre from polyethylene terephthalate (PET). Made from Autex Cube™ which contains a minimum of 45% previously recycled polyester fibre.

SUITABLE APPLICATIONS

Suspended or direct fix with patented aluminium channels and connector clips.

COLOUR FASTNESS TO LIGHT

Frontier is suitable for indoor use only. Light fastness is dependent on use and exposure. Frontier has been evaluated to the following standard:

ISO 105-B02:2014

Rating: 6 (Highest = 7)

FIRE RATING

Frontier is a value-added product made from Autex Cube™ as the base material. Cube™ has been evaluated using the following test methods:

ISO 9705: 1993

Classification: Group 1-S

Smoke Production Rate: <5.0m²/s

As required by NZBC C/VM2

AS ISO 9705 - 2003

Classification: Group 1

(SMOGR_{Arc}): <100m²/s²

Assessed using methodology AS ISO 9705:2003 in accordance with AS 5637.1:2015, as required by BCA Specification C1.10-4

Fl 4974 dated 16th September, 2012 and FAR 4055-2 dated 8th

October, 2013

BS EN 13501-1:2018

Wall applications

Classification: B-s2,d0 (Cube™ 12mm)

Tested using BS EN ISO 11925-2:2020 and BS EN 13823:2020 and classified in accordance with BS EN 13501-1:2018, as required by BS EN 15102:2007 + A1:2011. EUI-20-000268-A

Ceiling applications

Classification: B-s2,d0 (Cube™ 12mm)

Tested using BS EN ISO 11925-2:2020 and BS EN 13823:2020 and classified in accordance with BS EN 13501-1:2018, as required by BS EN 13964:2014. EUI-20-000268-B

ASTM E-84-15a

Class A, FS:0 - SD:45

RJ4479:2 dated 25th January, 2016

ACOUSTIC PERFORMANCE

Frontier Acoustic Raft is specifically designed to reduce and control reverberating noise in building interiors.

Sound Absorption Coefficients according to ISO 354.

DESCRIPTION	University of Auckland Test report number	FREQUENCY (Hz)						
		125	250	500	1000	2000	4000	NRC
Frontier Acoustic Raft 12mm Trapezoid, 300 centres	T1905-11	0.25	0.65	0.85	1.05	1.15	1.15	0.95
Frontier Acoustic Raft 12mm Blade, 300 centres	T1905-10	0.20	0.35	0.60	1.00	1.25	1.25	0.80
Frontier Acoustic Raft 12mm Beam 100, 150 centres	T1945-4	0.05	0.25	0.55	0.95	1.15	1.20	0.75
Frontier Acoustic Raft 12mm Beam 250, 300 centres	T1945-5	0.20	0.45	0.70	1.10	1.35	1.30	0.90

VOC EMISSIONS

Autex polyester has been tested for chemical emissions in accordance with ASTM D5116 and is considered as a low VOC product.

VOC concentration: 0.009 mg/m³ (7 days)

FINISH

Frontier Acoustic Raft does not have a pattern repeat, but it does have a directional grain. The product may vary from samples and batch to batch due to fibre blending and lay-up, which is an inherent feature of this product.

PHYSICAL DESCRIPTION / PROPERTIES

Boiling Point:	N/A
Melting Point:	250°C 482°F
Vapour Pressure:	N/A
Specific Gravity:	Polyester 1.38
Flash point:	N/A
Explosive limits:	N/A
Solubility in water:	Not soluble
Alkalinity:	pH 7.8
Relative Vapour Density:	N/A

CARE AND MAINTENANCE

Maintain in accordance with the Care and Maintenance Guide available for this product.

AUTEX 

www.autexglobal.com

AN ISO 9001 AND ISO 14001 CERTIFIED COMPANY

Autex Industries Ltd
702-718 Rosebank Rd,
Private Bag 19988,
Avondale 1746, Auckland,
New Zealand
Freephone **0800 428 839**
Phone **+64 9 828 9179**
Fax **+64 9 828 5810**

Autex Australia Pty Ltd
166 Bamfield Road,
PO Box 5099,
West Heidelberg, Melbourne,
VIC 3081, Australia
Freephone **1800 678 160**
Phone **+61 3 9457 6700**
Fax **+61 3 9457 1020**

Autex Acoustics Ltd
Unit J4, Lowfields Way,
Lowfields Business Park,
Elland, West Yorkshire,
HX5 9Da,
United Kingdom
Phone **+44 0 1422 418899**

Autex Acoustics LLC
19350 Van Ness Avenue
Torrance, CA 90501
United States of America
Phone **+1 424 203 1813**

The brand names and logos mentioned herein are registered or unregistered trademarks either owned or used under license by Autex Industries Limited or other members of the Autex Group. The contents of this document are protected by Copyright 2020 Autex Industries Ltd. All Rights Reserved.

It is the user's responsibility to determine if the product and information presented in this document is suitable for the intended application by engaging a suitably qualified consultant. The information contained in this document is correct to the best of our knowledge at the date of its publication. To verify that this document is the most current publication please check our website or contact your Autex account manager.